



All dimensions shown are in millimetres

All steel construction: **70mm x 11mm ribs
dia 38mm headers**

Connections: **1.2m long flying lead (2 core)**

Model	Height ± 2mm	Width ± 2mm	Number of Tubes	Output Watts	Weight kg
ROEM180-075/GF	1817	740	6	1000	44.0

Issue 1.0



Tools & Material Required

Tape measure
Electric drill
Masonry drill bit
Screwdriver
Allen key
Spirit level
Stepladder (for taller radiators)

Key	Component	Qty
A	Wall Plug*	7
B	Main Bracket	1
C	Securing Bracket	7
D	Screw - 6mm dia x 50mm*	7
E	Grub Screw	1

* Wall Plugs & Screws not supplied

Assembly Instructions

Accurately mark out bracket holes on wall using spirit level.

Drill seven holes & insert wall plugs (A).

Attach main bracket (B) & securing bracket (C) to wall with screws (D).

Hang radiator onto hinge pins on main bracket. Rotate radiator towards wall until locking pin on radiator locates in securing bracket (C).

Secure in position by tightening grub screw (E) with allen key.

Electric radiators should be fitted only by a qualified electrician and must be earthed and connected to a cable outlet in the bathroom in accordance with I.E.E. wiring regulations. The electrical connection should be made to a '5 amp fused fixed spur' located outside the bathroom.

Note: for maintenance purposes, cable outlets must remain accessible and cables must not be buried directly into walls.

