## Zehnder Subway Electric





All dimensions shown are in millimetres

All steel construction: dia 23mm horizontal tubes 30mm x 30mm headers

Connections:

1.2m long flying lead (2 core)

Model	<b>Height*</b> ± 2mm	Width ± 2mm	Finish	<b>Output</b> Watts	<b>Weight</b> kg
SUBSS130045EAZK	1261	450	painted	500	12.2
SUBSS150045EAZK	1549	450	painted	600	14.7
SUBSS150060EAZK	1549	600	painted	750	17.9
SUBSS180060EAZK	1837	600	painted	900	21.0
SUBCS130045EAZK	1261	450	chrome	300	12.2
SUBCS150045EAZK	1549	450	chrome	300	14.7
SUBCS150060EAZK	1549	600	chrome	500	17.9
SUBCS180060EAZK	1837	600	chrome	600	21.0
SUBE-130-045/GF	1261	450	painted	500	12.6
SUBE-150-045/GF	1549	450	painted	600	15.3
SUBE-150-060/GF	1549	600	painted	750	18.3
SUBE-180-060/GF	1837	600	painted	900	21.1
SUBEC-130-045/GF	1261	450	chrome	300	12.6
SUBEC-150-045/GF	1549	450	chrome	300	15.3
SUBEC-150-060/GF	1549	600	chrome	500	18.3
SUBEC-180-060/GF	1837	600	chrome	600	21.1



Concept House Watchmoor Point Camberley Surrey GU15 3AD Tel: 01276 605800 Fax: 01276 24058 retailsales@zehnder.co.uk www.zehnder.co.uk Issue 1.0

Registered in England: 2296696

\* does not include immersion heater

## Zehnder Subway Electric



## **Tools & Material Required**

Tape measure Spanner - 13mm & 14mm Screwdriver - crosshead Pliers Electric drill Masonry drill bit Spirit level Stepladder (for taller radiators)

Key	Component	Qty
Α	Boss	4
В	Wall Plug	4
С	Bracket	4
D	Screw, 6mm dia x 50mm	4
Е	Washer	4
F	Grub Screw	4
G	Allen Key	1

## Assembly Instructions

Screw bosses (A) to studs on the back of the radiator. Accurately mark out bracket holes on wall using spirit level. Drill four holes to a minimum depth of 65mm & insert wall plugs (B). Attach brackets (C) to wall with screws (D) & washers (E). Hang radiator onto wall by inserting bosses (A) into brackets (C). Tighten grub screws (F) with Allen key (G).

Electric radiators should be fitted only by a qualified electrician and must be earthed and connected to a cable outlet in the bathroom in accordance with I.E.E. wiring regulations. The electrical connection should be made to a '5 amp fused fixed spur' located outside the bathroom.

Note: for maintenance purposes, cable outlets must remain accessible and cables must not be buried directly into walls.





Concept House Watchmoor Point Camberley Surrey GU15 3AD Tel: 01276 605800 Fax: 01276 24058 retailsales@zehnder.co.uk www.zehnder.co.uk